



Bearing Rolamentos do Brasil Ltda.

KOYO K25X35X30H needle roller bearings



Bearing No. K25X35X30H

Bore Diameter	25 mm
Outer Diameter	35 mm
Fw	25 mm
Ew	35 mm
Bc	30 mm
Weight	0.060 Kg
Basic dynamic load rating (C)	44.6 kN
Basic static load rating (C0)	57.2 kN
(Grease) Lubrication Speed	12000 r/min
(Oil) Lubrication Speed	19000 r/min
Category	Needle Non Thrust Roller Bearings
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.06
Product Group	B04144
Rolling Element	Needle Roller Bearing
Component	Roller Assembly Only
Enclosure	Not Applicable
Self Aligning	No
Retainer	Yes
Number of Rows of Rollers	Single Row
Separable	No
Closed End	Not Applicable
Inch - Metric	Metric

K25X35X30H Bearing 2D drawings and 3D CAD models



Bearing Rolamentos do Brasil Ltda.

Thrust Bearing	No
Long Description	25MM Bore; 35MM Outside Diameter; 30MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Other Features	Radial Roller Hardened Steel Cage
Category	Needle Non Thrust Roller Bearing
UNSPSC	31171512
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Needle
Manufacturer URL	http://www.koyousa.com
Manufacturer Item Number	K25X35X30H
Weight / LBS	0.132
Outside Diameter	1.378 Inch 35 Millimeter
Bore	0.984 Inch 25 Millimeter
Width	1.181 Inch 30 Millimeter
Bearing No.	K25X35X30H
Cr	44.6
C0r	57.2
Cu	9.00
Grease lub.	12000
Oil lub.	19000
P/S	S
(Refer.)Mass(kg)	0.060
Shaft(max.)	25.000
Shaft(min.)	24.991
Housing(max.)	35.025
Housing(min.)	35.009